

# EM 936

|                     |   |
|---------------------|---|
| <b>TIRE SIZE</b>    | <b>20 - 24</b>                            |
| <b>UM</b>           | IS STANDARD                               |
| <b>CONSTRUCTION</b> | ⊠ BIAS                                    |
| <b>MACHINERY</b>    | PALA EXCAVADORA / ELEVADOR<br>TELESCÓPICO |
| <b>VERSIÓN</b>      | STANDARD                                  |
| <b>TIRE TYPE</b>    | TL  |
| <b>LI/SS</b>        | 158 B ; 173 A2                            |



## DIMENSIONES IS STANDARD

|                 |             |                 |          |
|-----------------|-------------|-----------------|----------|
| <b>OD (MM)</b>  | 1390        | <b>PR</b>       | 12       |
| <b>SLR (MM)</b> | 665         | <b>TRA CODE</b> | E2/G2/L2 |
| <b>RC (MM)</b>  | 4205        |                 |          |
| <b>RIM REC</b>  | 16.00 T SDC |                 |          |

## LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 2.50 | 3.00 |
|------------|------|------|
| 50         | 4250 | -    |
| 10         | -    | 6500 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.