


AGRIMAX V- FLECTO



| | |
|--------------|--|
| TIRE SIZE | VF 600/70 R 28 NRO |
| UM | IS STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | TRATOR DE ALTA POTENCIA / TRATOR |
| VERSÃO | STANDARD |
| TIRE TYPE | TL |
| LI/SS | 167 D |

DIMENSÕES IS STANDARD

| | | | |
|----------|------|---------|-----------------|
| SW (MM) | 603 | RIM REC | DW 21 B |
| OD (MM) | 1551 | RIM ALT | DW 20 B |
| SLR (MM) | 662 | ECE | E11-106R-008814 |
| RC (MM) | 4596 | SRI | 725 |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 0.6 | 0.8 | 1.0 | 1.2 | 1.4 | 1.6 | 2.0 |
|--------------------------------|------|------|------|------|------|------|------|
| 70 | 2425 | 2820 | 3270 | 3665 | 4060 | 4455 | 4955 |
| FROM 65 TO 40 | 2670 | 3105 | 3595 | 4030 | 4465 | 4905 | 5450 |
| 30 | 2720 | 3165 | 3665 | 4110 | 4555 | 4995 | 5555 |
| 20 | 2775 | 3225 | 3735 | 4190 | 4645 | 5095 | 5665 |
| 10 | 2935 | 3415 | 3955 | 4435 | 4915 | 5395 | 5995 |
| *UPTO 10 CYC WITH FRONT LOADER | 3735 | 4345 | 5035 | 5645 | 6255 | 6865 | 7630 |
| 10 HT | 2720 | 3165 | 3665 | 4110 | 4555 | 4995 | 5555 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.