DATA SHEET

Ultimo aggiornam
2-06-2026

AGRIMAX RT 765

TIRE SIZE	**280/70 R 18**
UM	IS STANDARD
CONSTRUCTION	RADIAL
MACHINERY	IRRORAZIONE / TRATTORE / VENDEMMIATRICE / MIETITREBBIA / ATTREZZI AGRICOLI
VERSIONE	STANDARD
TIRE TYPE	TL
LI/SS	114 A8/B

DIMENSIONI IS STANDARD

SW (MM)	275	**RIM REC**	W 9
OD (MM)	849	**RIM ALT**	W 8 ; W 10
SLR (MM)	381	**ECE**	E4-106R-000635
RC (MM)	2547	**SRI**	400

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
50	555	640	735	830	925	1015	1100	1180
40	555	640	735	830	925	1015	1100	1180
30	595	685	785	890	990	1090	1180	1265
10 LT	745	860	985	1110	1240	1365	1475	1585
10 HT	595	685	785	890	990	1090	1180	1265

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..