


RIDEMAX FL 693 M



TIRE SIZE	500/60 R 22.5
UM	IS STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	TANKBIL / SLÄPVAGN / ARBETSFORDON
VERSION	STANDARD
TIRE TYPE	TL
LI/SS	163 D

DIMENSIONER IS STANDARD

SW (MM)	503	RIM REC	AG 16.00
OD (MM)	1172	RIM ALT	15.00; 17.00
SLR (MM)	544	ECE	E11-106R-007203
RC (MM)	3625	SRI	550

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	1.2	1.6	2	2.4	2.8	3.2	3.6	4	4.5	5	5.5	6.0
70	1470	1825	2000	2310	2620	2890	3155	3465	3690	3910	4175	4440
65	1610	2000	2195	2535	2880	3170	3465	3805	4050	4290	4585	4875
50	1950	2420	2655	3070	3485	3835	4190	4605	4900	5195	5550	5900
40	2190	2720	2985	3450	3915	4310	4710	5175	5505	5835	6235	6630
25	2545	3160	3470	4010	4550	5010	5475	6010	6400	6785	7245	7705
10	2900	3600	3950	4565	5180	5705	6235	6845	7285	7725	8250	8775

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.