


FL 639

TIRE SIZE	800/40 R 22.5
UM	IS STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	STREUMASCHINE / LANDWIRTSCHAFTLICHE GERÄTE
VERSION	STANDARD
TIRE TYPE	TL
LI/SS	168 D ; 178 A8



ABMESSUNGEN IS STANDARD

SW (MM)	828	RIM REC	AG 28.00
OD (MM)	1212	ECE	E11-106R-0010830
SLR (MM)	538	SRI	575
RC (MM)	3642		

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.8	1.2	1.6	2.0	2.4	2.8	3.2	3.6	4.0
70	1635	2095	2605	2960	3420	3880	4235	4645	5100
65	1795	2300	2860	3250	3755	4260	4650	5100	5600
50	2170	2780	3460	3935	4545	5155	5630	6170	6780
40	2400	3075	3825	4350	5025	5700	6225	6825	7500
30	2710	3470	4315	4910	5670	6430	7025	7700	8460
25	2835	3630	4515	5135	5930	6730	7350	8055	8850
10	3230	4135	5145	5850	6755	7665	8370	9175	10080

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.