


# AGRIMAX SIRIO

<b>TIRE SIZE</b>	<b>IF 600/70 R 30</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	ТРАКТОР ВЫСОКОЙ МОЩНОСТИ / ТРАКТОР-ТЯГАЧ
<b>VERSION</b>	HIGH SPEED
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	165 D ; 162 E



## РАЗМЕРЫ IS STANDARD

<b>SW (MM)</b>	603	<b>RIM REC</b>	DW 21 B
<b>OD (MM)</b>	1602	<b>RIM ALT</b>	DW 20 B
<b>SLR (MM)</b>	713	<b>ECE</b>	E4-106R-000817
<b>RC (MM)</b>	4759	<b>SRI</b>	750

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
70	2200	2525	2900	3280	3650	4025	4350	4685
<b>FROM 65 TO 40</b>	2420	2780	3190	3605	4015	4425	4785	5150
30	2515	2890	3315	3745	4175	4600	4975	5355
25	2565	2945	3380	3820	4255	4690	5165	5560
20	2610	3000	3445	3890	4355	4775	5165	5560
10	3070	3530	4050	4575	5095	5615	6075	6540

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.