

# CON STAR

<b>TIRE SIZE</b>	<b>440/80 - 28</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 BIAS
<b>MACHINERY</b>	КОМПАКТНЫЙ ПОГРУЗЧИК / ТЕЛЕСКОПИЧЕСКИЙ ПОГРУЗЧИК / КОМПАКТНЫЙ ПОГРУЗЧИК / ТЕЛЕСКОПИЧЕСКИЙ ПОГРУЗЧИК
<b>VERSION</b>	INDUSTRIAL
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	156 A8



## РАЗМЕРЫ IS STANDARD

<b>SW (MM)</b>	450	<b>RIM REC</b>	DW 14 L
<b>OD (MM)</b>	1420	<b>RIM ALT</b>	DW 13; DW 13 L; DW 15 L
<b>SLR (MM)</b>	632	<b>ECE</b>	E11-106R-003035
<b>RC (MM)</b>	4299	<b>SRI</b>	675

## LOAD CAPACITY (KG/TIRE)

<b>KM/H / BAR</b>	<b>3.20</b>
40	4000

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.