


FL 635

| | |
|---------------------|--|
| TIRE SIZE | 750/45 R 22.5 |
| UM | US STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | BALPRESS / SKÖRDEMASKIN |
| VERSION | STANDARD |
| TIRE TYPE | TL |
| LI/SS | 168 D |



DIMENSIONER US STANDARD

| | | | |
|-----------------|----------|----------------|----------------|
| USA CODE | 94048786 | RC (IN) | 150.0 |
| SW (IN) | 29.7 | RIM REC | AG 24.00 |
| OD (IN) | 49.1 | ECE | E4-106R-002653 |
| SLR (IN) | 21.9 | | |

LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 12 | 15 | 17 | 23 | 29 | 35 | 41 | 46 | 52 | 58 |
|-----------|------|------|------|-------|-------|-------|-------|-------|-------|-------|
| 45 | 3600 | 4110 | 4620 | 5740 | 6530 | 7540 | 8550 | 9340 | 10240 | 11240 |
| 40 | 3960 | 4520 | 5070 | 6300 | 7160 | 8280 | 9390 | 10250 | 11240 | 12350 |
| 30 | 4780 | 5460 | 6130 | 7630 | 8670 | 10020 | 11360 | 12410 | 13600 | 14950 |
| 25 | 5380 | 6140 | 6890 | 8580 | 9740 | 11260 | 12780 | 13940 | 15290 | 16800 |
| 20 | 5970 | 6810 | 7650 | 9510 | 10820 | 12500 | 14170 | 15490 | 16970 | 18650 |
| 15 | 6250 | 7130 | 8000 | 9950 | 11320 | 13070 | 14840 | 16200 | 17760 | 19510 |
| 5 | 7120 | 8120 | 9120 | 11340 | 12900 | 14890 | 16900 | 18450 | 20230 | 22220 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.