

# AW 702

<b>TIRE SIZE</b>	<b>10.5/65 - 16</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	❖ BIAS
<b>MACHINERY</b>	PRESSA PER BALLE DI FIENO / ATTREZZI AGRICOLI / RIMORCHIO / MIETITREBBIA / ATTREZZI AGRICOLI / RIMORCHIO
<b>VERSIONE</b>	STANDARD
<b>TIRE TYPE</b>	TT
<b>LI/SS FREE ROLLING</b>	130 A8



## DIMENSIONI US STANDARD

<b>CODICE USA</b>	94009275	<b>RC (IN)</b>	91.7
<b>SW (IN)</b>	10.6	<b>RIM REC</b>	W 9
<b>OD (IN)</b>	29.9	<b>RIM ALT</b>	W 8; W 8 L
<b>SLR (IN)</b>	13.8	<b>ECE</b>	E11-106R-003351

## LOAD CAPACITY (LBS/TIRE)

<b>MPH / PSI</b>	<b>77</b>
<b>5 FR</b>	5860
<b>15 FR</b>	4980
<b>20 FR</b>	4700
<b>25 FR</b>	4190

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.