


EARTHMAX SR 30

| | |
|---------------------|--|
| TIRE SIZE | 15.5 R 25 |
| UM | IS STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | ARTICULATED DUMP TRUCK / DOZER / LOADER |
| VERSION | CUT RESISTANT COMPOUND |
| TIRE TYPE | TL |
| LI/SS | 160 B ; 169 A2 |



DIMENSIONS IS STANDARD

| | | | |
|-----------------|-----------|--------------------|-------|
| OD (MM) | 1276 | TRA CODE | E3/L3 |
| SLR (MM) | 574 | STAR RATING | ★★★ |
| RC (MM) | 3809 | | |
| RIM REC | 12.00/1.3 | | |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 4.00 | 4.25 | 4.50 | 4.75 | 5.00 | 5.25 |
|------------|------|------|------|------|------|------|
| 50 | 3650 | 3875 | 4000 | 4250 | 4375 | 4500 |
| 10 | 5000 | 5150 | 5450 | 5600 | 5800 | - |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.