

AGRIMAX RT 955

| | |
|---------------------|--|
| TIRE SIZE | 300/95 R 46 |
| UM | IS STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | ОПРЫСКИВАТЕЛЬ / КОМБАЙН ДЛЯ УБОРКИ ВИНОГРАДА / КОМБАЙН / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ |
| VERSION | STANDARD |
| TIRE TYPE | TL |
| LI/SS | 148 A8/B |



РАЗМЕРЫ IS STANDARD

| | | | |
|-----------------|------|----------------|--------------------------|
| SW (MM) | 295 | RIM REC | W 9 |
| OD (MM) | 1738 | RIM ALT | W 10; W 11; DW 10; DW 11 |
| SLR (MM) | 812 | ECE | E4-106R-000790 |
| RC (MM) | 5318 | SRI | 825 |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 0.6 | 0.8 | 1.0 | 1.2 | 1.4 | 1.6 | 2.0 | 2.4 | 2.8 | 3.2 | 3.6 | 4.0 | 4.4 |
|------------|------|------|------|------|------|------|------|------|------|------|------|------|------|
| 50 | 1105 | 1295 | 1485 | 1670 | 1860 | 2020 | 2205 | 2365 | 2585 | 2805 | 2995 | 3150 | - |
| 40 | 1105 | 1295 | 1485 | 1670 | 1860 | 2020 | 2205 | 2365 | 2585 | 2805 | 2995 | 3150 | - |
| 30 | 1185 | 1385 | 1590 | 1790 | 1995 | 2160 | 2365 | 2535 | 2770 | 3005 | 3210 | 3375 | - |
| 20 | 1360 | 1590 | 1825 | 2055 | 2290 | 2480 | 2715 | 2910 | 3180 | 3450 | 3685 | 3875 | - |
| 10 | 1525 | 1785 | 2045 | 2310 | 2570 | 2785 | 3045 | 3265 | 3570 | 3875 | 4135 | 4350 | 4725 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.