

# ROCK GRIP E4

|                     |                   |
|---------------------|-------------------|
| <b>TYRE SIZE</b>    | <b>30.00 - 51</b> |
| <b>UM</b>           | IS STANDARD       |
| <b>CONSTRUCTION</b> | ⊠ BIAS            |
| <b>MACHINERY</b>    | RIGID DUMP TRUCK  |
| <b>VERSION</b>      | STANDARD          |
| <b>TYRE TYPE</b>    | TL                |



## DIMENSIONS IS STANDARD

|                 |           |                 |    |
|-----------------|-----------|-----------------|----|
| <b>OD (MM)</b>  | 2910      | <b>PR</b>       | 46 |
| <b>SLR (MM)</b> | 1350      | <b>TRA CODE</b> | E4 |
| <b>RC (MM)</b>  | 8615      |                 |    |
| <b>RIM REC</b>  | 22.00/4.5 |                 |    |

## LOAD CAPACITY (KG/TYRE)

| <b>KM/H / BAR</b> | <b>5.00</b> | <b>6.50</b> |
|-------------------|-------------|-------------|
| 50                | 29000       | -           |
| 10                | -           | 48750       |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.