DATA SHEET

PRINTED ON
21-04-2026

EARTHMAX SR 468

TIRE SIZE	**40.00 R 57**
UM	US STANDARD
CONSTRUCTION	RADIAL
MACHINERY	RIGID DUMP TRUCK
VERSION	CUT RESISTANT COMPOUND
TIRE TYPE	TL
LI/SS	250 B

DIMENSIONS US STANDARD

USA CODE	94068845	**RIM REC**	29.00/6.0
OD (IN)	140.7	**RIM ALT**	32.00/6.0
SLR (IN)	62.8	**TRA CODE**	E4
RC (IN)	421.3	**STAR RATING**	★★

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	80	83	87	91	94	98	102
30	110000	113500	117000	120000	123500	128000	132500

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..