


# AW 711

**380/70 R 19.5**

<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	BIÇERDÖVER / UYGULAMALI MAKINE / BIÇERDÖVER / UYGULAMALI MAKINE
<b>VERSION</b>	STUBBLE RESISTANT
<b>TIRE TYPE</b>	TL
	159 A8/B



## UNDEFINED US STANDARD

<b>USA CODE</b>	94066605	<b>RC (IN)</b>	119.6
<b>SW (IN)</b>	15.3	<b>RIM REC</b>	11.75
<b>OD (IN)</b>	40.1	<b>RIM ALT</b>	12.75
<b>SLR (IN)</b>	17.5	<b>ECE</b>	E11-106R-006808

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	12	17	23	29	35	41	46	52	58	73	80
30	2850	3670	4490	5170	5990	6800	7290	8060	8830	9070	9640
25	2850	3670	4490	5170	5990	6800	7290	8060	8830	9070	9640
20	3200	4110	5030	5790	6700	7620	8160	9030	9890	10160	10800
15	3390	4360	5350	6150	7130	8100	8670	9600	10520	10800	11490
10	3590	4630	5650	6510	7540	8580	9180	10160	11130	11430	12160
5	3990	5140	6280	7230	8380	9520	10200	11280	12360	12700	13500

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.