


# AS 504

<b>TIRE SIZE</b>	<b>6.00 - 16</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 BIAS
<b>MACHINERY</b>	TELESKOPLADER / FELD-ANHÄNGER / LANDWIRTSCHAFTLICHE GERÄTE / TELESKOPLADER
<b>VERSION</b>	HD
<b>TIRE TYPE</b>	TT
<b>LI/SS DRIVE WHEEL</b>	91 A8
<b>LI/SS FREE ROLLING</b>	103 A8



## ABMESSUNGEN IS STANDARD

<b>SW (MM)</b>	164	<b>RIM REC</b>	4.00 E
<b>OD (MM)</b>	735	<b>RIM ALT</b>	4.50 E; 4½ K
<b>SLR (MM)</b>	343	<b>ECE</b>	E11-106R-005195
<b>RC (MM)</b>	2190	<b>PR</b>	8

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	4.00
10 FR	1225
25 FR	1040
30 FR	980
40 FR	875
10 DW	860
25 DW	730
30 DW	690
40 DW	615

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.