

AGRIMAX V- FLECTO

VF 540/65 R 38

| | |
|---------------------|--|
| UM | US STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | YÜKSEK GÜÇTE TRAKTÖR / TRAKTÖR |
| VERSION | STANDARD |
| TIRE TYPE | TL |
| | 162 D |



UNDEFINED US STANDARD

| | | | |
|-----------------|----------|----------------|-----------------|
| USA CODE | 94059119 | RC (IN) | 196.1 |
| SW (IN) | 21.6 | RIM REC | DW 20 B |
| OD (IN) | 66.0 | RIM ALT | DW 18 L |
| SLR (IN) | 29.9 | ECE | E11-106R-005020 |

LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 9 | 12 | 15 | 17 | 20 | 23 | 29 |
|--------------------------------------|------|------|------|-------|-------|-------|-------|
| 45 | 4850 | 5610 | 6370 | 7240 | 7900 | 8580 | 9520 |
| FROM 40 TO 25 | 5330 | 6170 | 7010 | 7960 | 8690 | 9420 | 10470 |
| 20 | 5430 | 6290 | 7140 | 8110 | 8850 | 9610 | 10680 |
| 12 | 5540 | 6420 | 7290 | 8270 | 9030 | 9800 | 10890 |
| 5 | 5860 | 6790 | 7700 | 8750 | 9550 | 10360 | 11520 |
| *UPTO 5 CYC WITH FRONT LOADER | 7460 | 8640 | 9810 | 11130 | 12160 | 13190 | 14660 |
| 5 HT | 5430 | 6290 | 7140 | 8110 | 8850 | 9610 | 10680 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.