

AGRIMAX RT 855

| | |
|---------------------|--|
| TIRE SIZE | 420/85 R 28 |
| UM | IS STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | ОПРЫСКИВАТЕЛЬ / КОМБАЙН ДЛЯ УБОРКИ ВИНОГРАДА / ТРАКТОР-ТЯГАЧ / КОМБАЙН / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ |
| VERSION | STANDARD |
| TIRE TYPE | TL |
| LI/SS | 139 A8/B |



РАЗМЕРЫ IS STANDARD

| | | | |
|-----------------|------|----------------|----------------|
| SW (MM) | 438 | RIM REC | W 15 L |
| OD (MM) | 1425 | RIM ALT | W 13; W 14 L |
| SLR (MM) | 638 | ECE | E4-106R-000602 |
| RC (MM) | 4241 | SRI | 675 |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 0.6 | 0.8 | 1.0 | 1.2 | 1.4 | 1.6 |
|------------|------|------|------|------|------|------|
| 50 | 1340 | 1560 | 1775 | 1995 | 2215 | 2430 |
| 40 | 1340 | 1560 | 1775 | 1995 | 2215 | 2430 |
| 30 | 1435 | 1670 | 1905 | 2140 | 2375 | 2605 |
| 10 LT | 1795 | 2090 | 2380 | 2675 | 2970 | 3260 |
| 10 HT | 1435 | 1670 | 1905 | 2140 | 2375 | 2605 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.