


AGRIMAX V-FLECTO

TIRE SIZE	VF 710/70 R 38
UM	US STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	TRACTEUR DE FORTE PUISSANCE / TRACTEUR
VERSION	STANDARD
TIRE TYPE	TL
LI/SS	181 D



DIMENSIONS US STANDARD

CODE USA	94063710	RC (IN)	227.3
SW (IN)	28.1	RIM REC	DW 24 B
OD (IN)	77.2	RIM ALT	DW 23 B; DW 25 B
SLR (IN)	33.2	ECE	E11-106R-006163

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	29
45	8270	9590	10910	12400	13720	15050	16540
FROM 40 TO 25	9090	10550	12000	13630	15090	16540	18190
20	9270	10760	12230	13900	15390	16880	18550
12	9460	10970	12480	14170	15690	17210	18910
5	10000	11600	13190	14990	16590	18200	20010
*UPTO 5 CYC WITH FRONT LOADER	12730	14760	16800	19080	21120	23160	25460
5 HT	9270	10760	12230	13900	15390	16880	18550

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.