


# AGRIMAX RT 855

<b>TIRE SIZE</b>	<b>340/85 R 28</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	IRRORAZIONE / VENDEMMIATRICE / TRATTORE / MIETITREBBIA / ATTREZZI AGRICOLI
<b>VERSIONE</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	139 A8/B



## DIMENSIONI US STANDARD

<b>CODICE USA</b>	94073269	<b>RC (IN)</b>	156.0
<b>SW (IN)</b>	13.9	<b>RIM REC</b>	W 12
<b>OD (IN)</b>	51.8	<b>RIM ALT</b>	W 11
<b>SLR (IN)</b>	23.7	<b>ECE</b>	E11-106R-008233

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	29	35	41	47
<b>30</b>	2090	2470	2840	3160	3540	3860	4230	4560	4980	5360
<b>25</b>	2090	2470	2840	3160	3540	3860	4230	4560	4980	5360
<b>20</b>	2250	2650	3050	3390	3790	4140	4540	4880	5350	5740
<b>5 LT</b>	2810	3310	3810	4240	4750	5180	5690	6120	6690	7190
<b>5 HT</b>	2250	2650	3050	3390	3790	4140	4540	4880	5350	5740

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.