


# AS 504

<b>TIRE SIZE</b>	<b>16.0/70 - 20</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 BIAS
<b>MACHINERY</b>	LEVANTADOR TELESCÓPICO / REBOQUE PARA OS CAMPOS / IMPLEMENTOS AGRÍCOLAS / LEVANTADOR TELESCÓPICO
<b>VERSÃO</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS DRIVE WHEEL</b>	142 A8
<b>LI/SS FREE ROLLING</b>	154 A8



## DIMENSÕES IS STANDARD

<b>SW (MM)</b>	418	<b>RIM REC</b>	13
<b>OD (MM)</b>	1097	<b>RIM ALT</b>	12 SDC; 14; 13 SDC
<b>SLR (MM)</b>	487	<b>ECE</b>	E4-106R-001876
<b>RC (MM)</b>	3214	<b>PR</b>	14

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	3.50
10 FR	5250
25 FR	4465
30 FR	4200
40 FR	3750
10 DW	3710
25 DW	3155
30 DW	2970
40 DW	2650

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.