


# AGRIMAX V- FLECTO

|              |  |
|--------------|--|
| TIRE SIZE    | VF 520/70 R 38   |
| UM           | US STANDARD  |
| CONSTRUCTION |  RADIAL |
| MACHINERY    | TRATOR DE ALTA POTENCIA / TRATOR   |
| VERSÃO       | SPECIAL  |
| TIRE TYPE    | TL   |
| LI/SS        | 164 D  |



## DIMENSÕES US STANDARD

|            |          |          |                  |
|------------|----------|----------|------------------|
| CÓDIGO USA | 94516124 | RC (IN)  | 205.2            |
| SW (IN)    | 21.1     | RIM REC  | DW 18 L          |
| OD (IN)    | 68.9     | ECE      | E11-106R-0011692 |
| SLR (IN)   | 30.4     | TRA CODE | R1W              |

## LOAD CAPACITY (LBS/TIRE)

| MPH / PSI     | 9    | 12   | 15    | 17    | 20    | 23    | 29    |
|---------------|------|------|-------|-------|-------|-------|-------|
| 45            | 5020 | 5820 | 6620  | 7530  | 8330  | 9140  | 10030 |
| FROM 40 TO 25 | 5510 | 6390 | 7270  | 8270  | 9150  | 10030 | 11020 |
| 20            | 5620 | 6530 | 7430  | 8430  | 9340  | 10240 | 11240 |
| 12            | 5730 | 6660 | 7570  | 8600  | 9520  | 10440 | 11460 |
| 5             | 6060 | 7030 | 8000  | 9090  | 10060 | 11030 | 12120 |
| 5 HT          | 5620 | 6520 | 7420  | 8430  | 9330  | 10230 | 11240 |
| UPTO 5 CYC    | 8190 | 9500 | 10810 | 12280 | 13590 | 14900 | 16370 |
| UPTO 10 CYC   | 7470 | 8660 | 9870  | 11210 | 12400 | 13600 | 14940 |
| UPTO 20 CYC   | 6260 | 7260 | 8270  | 9390  | 10390 | 11390 | 12510 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.