

RT 747 AGRO INDUSTRIAL

500/70 R 24**UM** IS STANDARD**CONSTRUCTION**  RADIAL**MACHINERY** KÜÇÜK YÜKLEYİCİ / TELESKOPIK
YÜKLEYİCİ / KÜÇÜK YÜKLEYİCİ /
TELESKOPIK YÜKLEYİCİ**VERSION** STANDARD**TIRE TYPE** TL

157 A8 ; 154 B



UNDEFINED IS STANDARD

| | | | |
|-----------------|------|----------------|-------------------|
| SW (MM) | 485 | RIM REC | DW 16 L |
| OD (MM) | 1320 | RIM ALT | DW 15 L ; DW 18 L |
| SLR (MM) | 585 | ECE | E11-106R-002988 |
| RC (MM) | 3949 | SRI | 625 |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 1.2 | 1.6 | 2.0 | 2.4 | 2.8 | 3.0 |
|------------|------|------|------|------|------|------|
| 50 | 1765 | 2175 | 2550 | 2965 | 3340 | 3750 |
| 40 | 1940 | 2395 | 2805 | 3260 | 3670 | 4125 |
| 30 | 2075 | 2560 | 3000 | 3490 | 3930 | 4415 |
| 25 | 2155 | 2655 | 3115 | 3620 | 4075 | 4580 |
| 10 CYC | 2910 | 3590 | 4210 | 4890 | 5510 | 6190 |
| STATIC | 4075 | 5025 | 5890 | 6845 | 7710 | 8665 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.