

AW 702

| | |
|---------------------------|--|
| TIRE SIZE | 10.0/80 - 12 |
| UM | US STANDARD |
| CONSTRUCTION | ❖ BIAS |
| MACHINERY | ENFARDADEIRA DE FENO / IMPLEMENTOS AGRÍCOLAS / REBOQUE / CEIFEIRA / IMPLEMENTOS AGRÍCOLAS / REBOQUE |
| VERSÃO | STANDARD |
| TIRE TYPE | TL |
| LI/SS FREE ROLLING | 116 A8 |



DIMENSÕES US STANDARD

| | | | |
|-------------------|----------|----------------|------|
| CÓDIGO USA | 94009152 | RC (IN) | 84.4 |
| SW (IN) | 10.4 | RIM REC | 9.00 |
| OD (IN) | 28.0 | RIM ALT | 7.0 |
| SLR (IN) | 12.5 | PR | 8 |

LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 45 |
|------------------|-----------|
| 5 FR | 3860 |
| 15 FR | 3280 |
| 20 FR | 3090 |
| 25 FR | 2760 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.