


FL 695

650/55 R 26.5

UM	US STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	RÖMORK / UYGULAMALI MAKINE / RÖMORK
VERSION	STEEL BELTED
TIRE TYPE	TL
	178 D



UNDEFINED US STANDARD

USA CODE	94067886	RC (IN)	167.0
SW (IN)	24.8	RIM REC	AG20.00
OD (IN)	54.7	RIM ALT	AG22.00
SLR (IN)	24.8	ECE	E11-106R-007052

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	12	17	23	29	35	41	46	52	58	65	73	80	87
40	--	--	--	7440	8600	9750	10750	11740	12900	13720	14550	15540	16530
30	--	--	--	9010	10410	11810	13010	14210	15610	16610	17610	18820	20010
25	--	7430	9230	10120	11690	13270	14620	15970	17550	18670	19800	21140	22490
20	6250	8240	10240	11240	12980	14740	16240	17740	19480	20720	21980	23480	24970
15	6540	8630	10710	11760	13590	15420	16990	18550	20380	21690	22990	24560	26120
10	6820	9010	11190	12280	14190	16100	17740	19380	21280	22650	24010	25650	27280
5	7440	9820	12200	13390	15480	17560	19340	21130	23210	24700	26190	27980	29760

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.