



PRINTED ON  
21-04-2026

## DATA SHEET

# TR 463

|                     |                                     |
|---------------------|-------------------------------------|
| <b>TIRE SIZE</b>    | <b>18.4 - 26</b>                    |
| <b>UM</b>           | US STANDARD                         |
| <b>CONSTRUCTION</b> |                                     |
| <b>MACHINERY</b>    | BACKHOE LOADER / INDUSTRIAL TRACTOR |
| <b>VERSION</b>      | INDUSTRIAL                          |
| <b>TIRE TYPE</b>    | TL                                  |
| <b>LI/SS</b>        | 158 A8                              |



### DIMENSIONS US STANDARD

|                 |          |                |                  |
|-----------------|----------|----------------|------------------|
| <b>USA CODE</b> | 94515073 | <b>RC (IN)</b> | 165.9            |
| <b>SW (IN)</b>  | 18.9     | <b>RIM REC</b> | DW 16 L          |
| <b>OD (IN)</b>  | 56.1     | <b>RIM ALT</b> | DW 15 L          |
| <b>SLR (IN)</b> | 25.1     | <b>ECE</b>     | E11-106R-0011590 |

### LOAD CAPACITY (LBS/TIRE)

|                  |           |
|------------------|-----------|
| <b>MPH / PSI</b> | <b>42</b> |
| 25               | 9350      |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.