



IS standard



GROWING TOGETHER

EARTHMAX

RADIAL OTR TIRES

SR 55 M



PRODUCT DATA SHEET

EARTHMAX SR 55 M
RADIAL OTR TIRES



EARTHMAX SR 55 M is an All-Steel radial tyre specifically engineered for wheel loaders and load haul dumps (LHD) operating in the most demanding underground mining and recycling environments. Thanks to the redesigned tread wear indicator - now integrated into the circumferential grooves - the tyre features a fully-closed, smooth tread pattern that significantly enhances resistance to damage and extends the tyre's service life. The extra tread depth further ensures that EARTHMAX SR 55 M delivers exceptional durability and minimizes the risk of cuts and tears, even in the harshest working conditions.



Radial



Technologies



Smooth Tyre



All Steel



Extra Deep Tread

Performance



Cut and Chip Resistance



High Puncture Resistance



Durability

	Tyre size	Type	TRA CODE	STAR RATING	LI/SS	Version	TKPH	O.W.	O.D.	SLR	RC	TREAD DEPTH (mm)	RIM	
								(mm)	(mm)	(mm)	(mm)		Rec.	Alt.
Ø 25"	17.5 R 25	TL	L-5S	***	188 A2	CRC	-	455	1400	630	4211	68	14.00/1.5	-

CRC: Cut Resistance Compound



Tolerances: O.D. ± 2% - O.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; O.W. = Overall Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference