


AGRIMAX RT 855

| | |
|---------------------|--|
| | 480/80 R 46 |
| UM | US STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | ILAÇLAMA / ÜZÜM HASAT MAKINESİ / TRAKTÖR / BIÇERDÖVER / UYGULAMALI MAKINE |
| VERSION | STANDARD |
| TIRE TYPE | TL |
| | 158 A8/B |



UNDEFINED US STANDARD

| | | | |
|-----------------|----------|----------------|----------------------------|
| USA CODE | 94021826 | RC (IN) | 231.1 |
| SW (IN) | 18.9 | RIM REC | DW 16 A ; W 16 A ; DD 16 |
| OD (IN) | 76.2 | RIM ALT | W 16 L ; DD 16 L ; DW 16 L |
| SLR (IN) | 35.2 | ECE | E4-106R-001731 |

LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 9 | 12 | 15 | 17 | 20 | 23 | 29 | 35 |
|-----------|------|------|------|------|------|-------|-------|-------|
| 30 | 4410 | 5060 | 5810 | 6560 | 7310 | 8060 | 8720 | 9350 |
| 25 | 4410 | 5060 | 5810 | 6560 | 7310 | 8060 | 8720 | 9350 |
| 20 | 4720 | 5420 | 6230 | 7020 | 7830 | 8630 | 9340 | 10030 |
| 5 LT | 5910 | 6790 | 7790 | 8800 | 9800 | 10800 | 11680 | 12550 |
| 5 HT | 4720 | 5420 | 6230 | 7020 | 7830 | 8630 | 9340 | 10030 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.