


MULTIMAX MP 527

TIRE SIZE	360/70 R 18 IND
UM	US STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	CARREGADORA COMPACTA / LEVANTADOR TELESCÓPICO / CARREGADORA COMPACTA / LEVANTADOR TELESCÓPICO
VERSÃO	STANDARD
TIRE TYPE	TL
LI/SS	142 A8/B



DIMENSÕES US STANDARD

CÓDIGO USA	94053650	RC (IN)	113.7
SW (IN)	14.2	RIM REC	11
OD (IN)	38.1	RIM ALT	W10 ; 11 SDC ; W11 ; 12 ; 12 SDC
SLR (IN)	17.3	ECE	E11-106R-002996

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	23	29	35	41	46	51	58	61	64
30	2810	3340	3800	4330	4850	5200	5840	-	-
25	2810	3340	3800	4330	4850	5200	5840	-	-
20	3010	3570	4080	4640	5200	5580	6260	-	-
15	3120	3700	4220	4810	5390	5790	6490	-	-
5 CYC.	3430	4210	4960	5700	6490	7050	7980	8420	8760
STATIC	5250	6460	7590	8740	9950	10820	12230	12910	13440

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.