

EARTHMAX SR 44



EARTHMAX
RADIAL OTR TIRES

EARTHMAX SR 44

EARTHMAX SR 44 (E-4) is an All Steel radial tyre suitable transport applications with tippers. The rugged E-4 tread pattern provides both excellent traction and operator comfort. EARTHMAX SR 44 (E-4) ensures also great high load capacity and extraordinary durability.



	SIZE	TT/TL	TRA CODE	PR	LI/SS	RIM		TKPH (TK/H)	OW (MM) (mm)	OD (mm)	SLR (mm)	RC (mm)	TREAD DEPTH (MM)	VERSION
						REC RIM	ALT RIM							
														
Ø16"	7.50 R 16	TT	-	-	122/118 G	6	5.5 6.5	0	226	820	380	2450	19	STD
Ø20"	12.00 R 20	TT	E4	-	-	8.50V	9.00V	0	305	1138	532	3408	25	STD
	10.00 R 20	TT	-	16	146/143 G	7.50	7.0 7.50VM 8.0	0	268	1075	505	3200	25	STD
	11.00 R 20	TT	E4	-	-	8.00	7.50 8.50 8.50VM	0	282	1111	520	3328	25,5	STD

STD: STANDARD

TECHNOLOGIES				PERFORMANCES			
							
							
G	158 kg						

Permissible tolerances: O.O. 2%–S.W. 2%–RC 2.5%–LI/SS load/speed index, S.W. tyre width O.O. outer diameter of the tyre: SLR static radius, RC rolling circumference ; SRI index

All images, texts and graphics contained in this document are the copyright of BKT. Permission is granted to print hard copies of this material. Any other form of reproduction, electronic or otherwise, as well as the application of any changes, partially or entirely, to images, texts, graphs and data is strictly prohibited without prior written permission by BKT. Balkrishna Industries Limited (BKT) reserves itself the right to alter any details contained in the publication without prior notice. BKT does not undertake any responsibility in relation to the exactness or correctness of information or illustrations contained in this document. BKT declines any direct or indirect liability for any material damage or personal injury which might arise directly or incidentally from the use of any information contained in this document. For any question in relation to specific operating issues always refer to the manufacturer of your vehicle or equipment.

GB – 23/09/2026

	SIZE	TT/TL	TRA CODE	PR	LI/SS	RIM		TKPH (TK/H)	OW (MM) (mm)	OD (mm)	SLR (mm)	RC (mm)	TREAD DEPTH (MM)	VERSION
						REC RIM	ALT RIM							
														
Ø24"	325/95 R 24 (12.00 R 24)	TL	E4	-	158 B	8.50V	9.00V	140	310	1250	575	3790	30,5	STD
	12.00 R 24 (325/95 R 24)	TT	E4	-	158 B	8.50V	9.00V	140	310	1250	575	3790	30,5	STD
	325/95 R 24 (12.00 R 24)	TT	E4	-	158 B	8.50V	9.00V	140	310	1250	575	3790	30,5	STD

STD: STANDARD



TECHNOLOGIES					PERFORMANCES			
								
								
G	158 kg							

Permissible tolerances: O.D. 2%–S.W. 2%–RC 2.5%–LI/SS load/speed index, S.W. tyre width O.O. outer diameter of the tyre: SLR static radius, RC rolling circumference ; SRI index

All images, texts and graphics contained in this document are the copyright of BKT. Permission is granted to print hard copies of this material. Any other form of reproduction, electronic or otherwise, as well as the application of any changes, partially or entirely, to images, texts, graphs and data is strictly prohibited without prior written permission by BKT. BKRishna Industries Limited (BKT) reserves itself the right to alter any details contained in the publication without prior notice. BKT does not undertake any responsibility in relation to the exactness or correctness of information or illustrations contained in this document. BKT declines any direct or indirect liability for any material damage or personal injury which might arise directly or incidentally from the use of any information contained in this document. For any question in relation to specific operating issues always refer to the manufacturer of your vehicle or equipment.

GB – 23/09/2026