

# AW 708

|                           |   |
|---------------------------|---|
| <b>TIRE SIZE</b>          | 19.0/45 - 17  |
| <b>UM</b>                 | US STANDARD   |
| <b>CONSTRUCTION</b>       | ⊠ BIAS  |
| <b>MACHINERY</b>          | BALPRESS / ARBETSFORDON /<br>SLÄPVAGN / SKÖRDEMASKIN /<br>ARBETSFORDON / SLÄPVAGN |
| <b>VERSION</b>            | SPECIAL   |
| <b>TIRE TYPE</b>          | TL  |
| <b>LI/SS FREE ROLLING</b> | 152 A8  |



## DIMENSIONER US STANDARD

|                 |          |                |                 |
|-----------------|----------|----------------|-----------------|
| <b>USA CODE</b> | 94063888 | <b>RC (IN)</b> | 99.8            |
| <b>SW (IN)</b>  | 19.3     | <b>RIM REC</b> | 16.00           |
| <b>OD (IN)</b>  | 34.1     | <b>ECE</b>     | E11-106R-003636 |
| <b>SLR (IN)</b> | 15.0     | <b>PR</b>      | 22              |

## LOAD CAPACITY (LBS/TIRE)

| <b>MPH / PSI</b> | <b>57</b> |
|------------------|-----------|
| 5 FR             | 10960     |
| 15 FR            | 9310      |
| 20 FR            | 8760      |
| 25 FR            | 7830      |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.