


# GR 288

|                     |  |
|---------------------|--|
| <b>TIRE SIZE</b>    | 20.5 - 25  |
| <b>UM</b>           | US STANDARD  |
| <b>CONSTRUCTION</b> |  BIAS |
| <b>MACHINERY</b>    | PALA CARICATRICE / DOZER /<br>MOTOLIVELLATRICE   |
| <b>VERSIONE</b>     | STANDARD   |
| <b>TIRE TYPE</b>    | TL   |



## DIMENSIONI US STANDARD

|                   |          |                |                 |
|-------------------|----------|----------------|-----------------|
| <b>CODICE USA</b> | 94035632 | <b>RIM REC</b> | 17.00/2.0       |
| <b>OD (IN)</b>    | 58.3     | <b>RIM ALT</b> | 17.00/1.7       |
| <b>SLR (IN)</b>   | 25.8     | <b>ECE</b>     | E11-106R-005180 |
| <b>RC (IN)</b>    | 173.1    | <b>PR</b>      | 20              |

## LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 40   | 65    |
|-----------|------|-------|
| 25        | 9900 | -     |
| 5         | -    | 20900 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.