


AGRIMAX RT 657

540/65 R 38

| | |
|---------------------|--|
| UM | US STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | ÜZÜM HASAT MAKINESİ / TRAKTÖR / BIÇERDÖVER |
| VERSION | SPECIAL |
| TIRE TYPE | TL |
| | 153 D ; 156 A8 |



UNDEFINED US STANDARD

| | | | |
|-----------------|----------|----------------|----------------|
| USA CODE | 94062652 | RC (IN) | 199.2 |
| SW (IN) | 20.9 | RIM REC | W 16 L |
| OD (IN) | 65.6 | RIM ALT | W 18 L |
| SLR (IN) | 29.9 | ECE | E4-106R-000589 |

LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 9 | 12 | 15 | 17 | 20 | 23 | 29 | 35 |
|-----------|------|------|------|------|------|------|------|-------|
| 40 | 3870 | 4510 | 5070 | 5630 | 6210 | 6680 | 7410 | 8050 |
| 30 | 4070 | 4740 | 5330 | 5920 | 6510 | 7020 | 7780 | 8450 |
| 25 | 4230 | 4940 | 5560 | 6170 | 6790 | 7320 | 8110 | 8820 |
| 20 | 4450 | 5190 | 5840 | 6480 | 7130 | 7690 | 8520 | 9260 |
| 5 LT | 5180 | 6050 | 6800 | 7560 | 8310 | 8960 | 9930 | 10790 |
| 5 HT | 4450 | 5190 | 5840 | 6480 | 7130 | 7690 | 8520 | 9260 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.