


AGRIMAX TURF RT 333

| | |
|---------------------|--|
| TYRE SIZE | 280/70 R 16 |
| UM | US STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | VINEYARD HARVESTER / ORCHARD HARVESTER / SMALL TRACTOR / TRACTOR / HARVESTER |
| VERSION | STANDARD |
| TYRE TYPE | TL |
| LI/SS | 112 A8 ; 112 B |



DIMENSIONS US STANDARD

| | | | |
|-----------------|----------|----------------|-----------------|
| USA CODE | 94065714 | RC (IN) | 93.3 |
| SW (IN) | 11.4 | RIM REC | W9 |
| OD (IN) | 31.5 | RIM ALT | W 8; W 10 |
| SLR (IN) | 14.1 | ECE | E11-106R-006472 |

LOAD CAPACITY (LBS/TYRE)

| MPH / PSI | 9 | 12 | 15 | 17 | 20 | 23 | 29 | 35 |
|-----------|------|------|------|------|------|------|------|------|
| 30 | 1170 | 1330 | 1530 | 1730 | 1930 | 2130 | 2330 | 2470 |
| 25 | 1170 | 1330 | 1530 | 1730 | 1930 | 2130 | 2330 | 2470 |
| 20 | 1250 | 1430 | 1640 | 1850 | 2070 | 2280 | 2490 | 2650 |
| 5 LT | 1570 | 1800 | 2060 | 2330 | 2590 | 2850 | 3120 | 3320 |
| 5 HT | 1250 | 1430 | 1640 | 1850 | 2070 | 2280 | 2490 | 2650 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.