

# XL GRIP (BHL)

|                     |                       |
|---------------------|-----------------------|
| <b>TIRE SIZE</b>    | <b>10.00 - 20</b>     |
| <b>UM</b>           | US STANDARD           |
| <b>CONSTRUCTION</b> | ⊠ BIAS                |
| <b>MACHINERY</b>    | GRÄVLASTARE           |
| <b>VERSION</b>      | ARAMID + STEEL BELTED |
| <b>TIRE TYPE</b>    | TT                    |



## DIMENSIONER US STANDARD

|                 |          |                |     |
|-----------------|----------|----------------|-----|
| <b>USA CODE</b> | 94050727 | <b>RIM REC</b> | 7.5 |
| <b>OD (IN)</b>  | 42.3     | <b>RIM ALT</b> | 7.0 |
| <b>SLR (IN)</b> | 19.9     | <b>PR</b>      | 18  |
| <b>RC (IN)</b>  | 128.2    |                |     |

## LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 120  | 110  |
|-----------|------|------|
| 5         | 9880 | -    |
| 25        | -    | 7290 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.