

FLOTATION 648

TIRE SIZE	500/50 - 17
UM	IS STANDARD
CONSTRUCTION	⊠ BIAS
MACHINERY	EMPACADORA DE HENO / COSECHADORA / ESPARCIDOR / COSECHADORA / MAQUINARIA AGRÍCOLA
VERSIÓN	STANDARD
TIRE TYPE	TL
LI/SS DRIVE WHEEL	137 A8/133 B
LI/SS FREE ROLLING	149 A8/145 B



DIMENSIONES IS STANDARD

SW (MM)	510	RIM REC	16.00
OD (MM)	945	ECE	E4-106R-001885
SLR (MM)	416	PR	14
RC (MM)	2750		

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	2.20	2.40	2.80
10 FR	3950	4160	4550
20 FR	3555	3740	4095
30 FR	3160	3325	3640
40 FR	2820	2970	3250
50 FR	2540	2675	2900
10 DW	2795	2940	3220
20 DW	2515	2645	2900
30 DW	2235	2350	2575
40 DW	1995	2100	2300
50 DW	1795	1890	2060

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.