

AGRIMAX RT 765

TIRE SIZE	360/70 R 20
UM	IS STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	BESPRUTNINGSBIL / TRAKTOR / SKÖRDEMASKIN FÖR VINGÅRD / SKÖRDEMASKIN / ARBETSFORDON
VERSION	STANDARD
TIRE TYPE	TL
LI/SS	129 A8/B



DIMENSIONER IS STANDARD

SW (MM)	357	RIM REC	W 11
OD (MM)	1042	RIM ALT	W 10; W 12
SLR (MM)	469	ECE	E4-106R-000647
RC (MM)	3122	SRI	475

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
50	870	1000	1150	1295	1445	1595	1725	1850
40	870	1000	1150	1295	1445	1595	1725	1850
30	935	1070	1230	1390	1545	1705	1845	1980
10 LT	1170	1340	1540	1740	1935	2135	2310	2480
10 HT	935	1070	1230	1390	1545	1705	1845	1980

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.