

EARTHMAX SR 35

| | |
|--------------|--|
| TIRE SIZE | 875/65 R 29 |
| UM | IS STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | ШАРНИРНО-СОЧЛЕНЕННЫЙ САМОСВАЛ / ПОГРУЗЧИК / БУЛЬДОЗЕР |
| VERSION | CUT RESISTANT COMPOUND |
| TIRE TYPE | TL |
| LI/SS | 203 B ; 214 A2 |



РАЗМЕРЫ IS STANDARD

| | | | |
|----------|------------|-------------|----------------------|
| OD (MM) | 1860 | RIM ALT | 27.00/3.0, 28.00/3.5 |
| SLR (MM) | 816 | TRA CODE | E3/L3 |
| RC (MM) | 5559 | STAR RATING | ★★/★ |
| RIM REC | 27.00/3.50 | | |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 4.00 | 4.25 | 4.50 | 4.75 |
|------------|-------|-------|-------|-------|
| 50 | 14000 | 14250 | 15100 | 15500 |
| 10 | 18500 | 19500 | 20600 | 21200 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.