


# AGRIMAX FORCE

|                     |  |
|---------------------|--|
| <b>TIRE SIZE</b>    | <b>IF 620/75 R 30</b>  |
| <b>UM</b>           | IS STANDARD  |
| <b>CONSTRUCTION</b> |  RADIAL |
| <b>MACHINERY</b>    | MIETITREBBIA / TRATTORE A ELEVATA POTENZA / TRATTORE                                     |
| <b>VERSIONE</b>     | STANDARD   |
| <b>TIRE TYPE</b>    | TL   |
| <b>LI/SS</b>        | 169 D  |



## DIMENSIONI IS STANDARD

|                 |      |                |                 |
|-----------------|------|----------------|-----------------|
| <b>SW (MM)</b>  | 650  | <b>RIM REC</b> | DW 23 B         |
| <b>OD (MM)</b>  | 1703 | <b>RIM ALT</b> | DW 21 B         |
| <b>SLR (MM)</b> | 759  | <b>ECE</b>     | E11-106R-006496 |
| <b>RC (MM)</b>  | 5100 | <b>SRI</b>     | 800             |

## LOAD CAPACITY (KG/TIRE)

| KM/H / BAR           | 0.6  | 0.8  | 1.0  | 1.2  | 1.4  | 1.6  | 2.0  | 2.4  |
|----------------------|------|------|------|------|------|------|------|------|
| 70                   | 2475 | 2845 | 3270 | 3690 | 4110 | 4535 | 4955 | 5275 |
| <b>FROM 65 TO 40</b> | 2725 | 3130 | 3595 | 4060 | 4520 | 4985 | 5450 | 5800 |
| 30                   | 2830 | 3288 | 3735 | 4220 | 4700 | 5180 | 5665 | 6030 |
| 20                   | 2940 | 3380 | 3880 | 4380 | 4880 | 5380 | 5885 | 6260 |
| 10                   | 3460 | 3975 | 4565 | 5155 | 5740 | 6330 | 6920 | 7365 |
| <b>UPTO 30 CYC</b>   | 3540 | 4065 | 4670 | 5275 | 5875 | 6480 | 7085 | 7540 |
| <b>UPTO 15 CYC</b>   | 4220 | 4850 | 5570 | 6290 | 7005 | 7725 | 8445 | 8990 |
| <b>UPTO 10 CYC</b>   | 4630 | 5320 | 6110 | 6900 | 7680 | 8470 | 9265 | 9860 |
| 10 HT                | 2830 | 3255 | 3735 | 4220 | 4700 | 5180 | 5665 | 6030 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.