

# SM 55 L5S

|                     |   |
|---------------------|---|
| <b>TIRE SIZE</b>    | 26.5 - 25   |
| <b>UM</b>           | US STANDARD   |
| <b>CONSTRUCTION</b> | BIAS  |
| <b>MACHINERY</b>    | VÉHICULE MINIERS SOUTERRAINS /<br>TOMBÉREAU SURBAISSÉ |
| <b>VERSION</b>      | ARASHIELD   |
| <b>TIRE TYPE</b>    | TL  |



## DIMENSIONS US STANDARD

|                 |          |                 |           |
|-----------------|----------|-----------------|-----------|
| <b>CODE USA</b> | 94052998 | <b>RIM REC</b>  | 22.00/3.0 |
| <b>OD (IN)</b>  | 70.8     | <b>PR</b>       | 36        |
| <b>SLR (IN)</b> | 32.1     | <b>TRA CODE</b> | L5S       |
| <b>RC (IN)</b>  | 209.5    |                 |           |

## LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 91    |
|-----------|-------|
| 5         | 40400 |
| 10        | 35100 |
| 15        | 32300 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.