



IS standard



GROWING TOGETHER

RIB IMPLEMENT (A)



PRODUCT DATA SHEET



Bias



A8



110

Performance



Handling and Comfort



Reduced Soil Compaction



RIB IMPLEMENT (A)

RIB IMPLEMENT (A) has been engineered for trailers and implement machinery in transport and soil tillage applications. It is ideal for modern farming and shows top performance both on and off the road. RIB IMPLEMENT (A) is the right choice for all operating conditions which require a high level of handling as well as reduced soil compaction to preserve the crops.

| | Tire size | RIM | | S.W. (mm) | O.D. (mm) | SLR (mm) | RC (mm) | Version | PR | Type | LI/SS | |
|-------|--------------|------|------|--------------|--------------|-------------|------------|---------|----|------|-------|-------|
| | | Rec. | Alt. | | | | | | | | DW | FR |
| | | | | | | | | | | | | |
| Ø 12" | 10.0/80 - 12 | 9.00 | 7.0 | 264 | 746 | 329 | 2186 | STD | 6 | TL | - | 110A8 |

STD: Standard



Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference; DW = Drive Wheel; FR = Free Rolling