


FL 639

TIRE SIZE	710/40 R 22.5
UM	IS STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	STREUMASCHINE / LANDWIRTSCHAFTLICHE GERÄTE
VERSION	STANDARD
TIRE TYPE	TL
LI/SS	161 D ; 172 AB



ABMESSUNGEN IS STANDARD

SW (MM)	727	RIM REC	AG 24.00
OD (MM)	1140	ECE	E4-106R-000801
SLR (MM)	503	SRI	550
RC (MM)	3492		

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.8	1.0	1.2	1.6	2.0	2.4	2.8	3.2	3.6	4.0
70	1350	1560	1770	2150	2485	2865	3245	3495	3875	4210
65	1480	1715	1945	2360	2730	3145	3565	3840	4255	4625
50	1795	2075	2355	2860	3305	3810	4315	4650	5155	5600
40	2015	2330	2645	3210	3715	4280	4845	5225	5790	6290
25	2340	2710	3075	3730	4315	4975	5630	6070	6730	7310
10	2665	3085	3500	4250	4915	5665	6415	6910	7660	8325

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.