

AGRIMAX RT 765

TIRE SIZE	650/75 R 42
UM	IS STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	PULVERIZADOR AGRÍCOLA / TRATOR / VINDIMADORA / CEIFEIRA / IMPLEMENTOS AGRÍCOLAS
VERSÃO	STANDARD
TIRE TYPE	TL
LI/SS	170 D



DIMENSÕES IS STANDARD

SW (MM)	655	RIM REC	DW21B
OD (MM)	2043	RIM ALT	DW20B;DW23B
SLR (MM)	916	ECE	E11-106R-006402
RC (MM)	6147	SRI	975

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
65	2820	3240	3720	4200	4680	5160	5640	6000
50	2965	3405	3910	4410	4915	5420	5925	6300
40	3090	3550	4075	4600	5125	5655	6180	6570
30	3245	3730	4280	4830	5385	5935	6490	6900
10 LT	3780	4345	4985	5630	6275	6915	7560	8040
10 HT	3245	3730	4280	4830	5385	5935	6490	6900

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.