

AS 504

TIRE SIZE	400/50 - 15
UM	US STANDARD
CONSTRUCTION	⊠ BIAS
MACHINERY	ТЕЛЕСКОПИЧЕСКИЙ ПОГРУЗЧИК / ПРИЦЕП ДЛЯ ПОЛЕВЫХ РАБОТ / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ / ТЕЛЕСКОПИЧЕСКИЙ ПОГРУЗЧИК
VERSION	STANDARD
TIRE TYPE	TL
LI/SS DRIVE WHEEL	109 A8
LI/SS FREE ROLLING	121 A8



РАЗМЕРЫ US STANDARD

USA CODE	94060092	RC (IN)	94.0
SW (IN)	15.6	RIM REC	13 LB
OD (IN)	31.1	ECE	E11-106R-005494
SLR (IN)	14.5		

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	44
5 FR	4480
15 FR	3800
20 FR	3580
25 FR	3200
5 DW	3170
15 DW	2700
20 DW	2550
25 DW	2270

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.