

# AGRIMAX RT 945

<b>TIRE SIZE</b>	<b>320/90 R 46</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	ОПРЫСКИВАТЕЛЬ / ТРАКТОР-ТЯГАЧ / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	148 D ; 151 A8



## РАЗМЕРЫ US STANDARD

<b>USA CODE</b>	94051694	<b>RC (IN)</b>	206.0
<b>SW (IN)</b>	12.6	<b>RIM REC</b>	W 10
<b>OD (IN)</b>	68.7	<b>RIM ALT</b>	W 9; W 11
<b>SLR (IN)</b>	31.9	<b>ECE</b>	E11-106R-004068

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	12	17	23	29	35	41	46	52
40	2990	3890	4730	5210	5490	6050	6540	6940
30	3140	4090	4970	5480	5760	6350	6870	7300
25	3270	4270	5180	5710	6020	6620	7150	7610
20	3440	4480	5430	5990	6300	6940	7510	7980
5	4490	5840	7090	7810	8230	9070	9800	10420

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.