

FL 630 SUPER

TIRE SIZE	650/55 R 26.5
UM	IS STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	РАЗБРАСЫВАТЕЛЬ / АВТОЦИСТЕРНА / ПРИЦЕП / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ
VERSION	HD
TIRE TYPE	TL
LI/SS	178 D



РАЗМЕРЫ IS STANDARD

SW (MM)	645	RIM REC	AG 20.00
OD (MM)	1389	ECE	E11-106R-003006
SLR (MM)	628	SRI	650
RC (MM)	4292		

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.8	1.0	1.2	1.6	2.0	2.4	2.8	3.2	3.6	4.0	5.0	6.0
65	1875	2325	2775	3375	3900	4500	5100	5475	6075	6675	7050	7500
50	2270	2815	3360	4085	4720	5445	6175	6625	7355	8080	8535	9075
40	2550	3165	3775	4590	5305	6120	6940	7450	8265	9080	9590	10200
30	2835	3515	4195	5100	5890	6795	7705	8270	9175	10080	10650	11325
25	2965	3675	4385	5335	6165	7110	8060	8655	9600	10550	11140	11850
10	3375	4185	4995	6075	7020	8100	9180	9855	10935	12015	12690	13500

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.