

## AGRIMAX RT 657

|                  |                                             |
|------------------|---------------------------------------------|
| <b>TIRE SIZE</b> | <b>540/65 R 24</b>                          |
| <b>UM</b>        | IS STANDARD                                 |
| <b>MACHINERY</b> | VENDEMMIATRICE / TRATTORE /<br>MIETITREBBIA |
| <b>VERSIONE</b>  | STANDARD                                    |
| <b>TIRE TYPE</b> | TL                                          |
| <b>LI/SS</b>     | 146 D ; 149 A8                              |



### DIMENSIONI IS STANDARD

|                 |      |                |                |
|-----------------|------|----------------|----------------|
| <b>SW (MM)</b>  | 530  | <b>RIM REC</b> | W 16 L         |
| <b>OD (MM)</b>  | 1312 | <b>RIM ALT</b> | W 18 L         |
| <b>SLR (MM)</b> | 596  | <b>ECE</b>     | E4-106R-000773 |
| <b>RC (MM)</b>  | 3942 | <b>SRI</b>     | 625            |

### LOAD CAPACITY (KG/TIRE)

| KM/H / BAR   | 0.6  | 0.8  | 1.0  | 1.2  | 1.4  | 1.6  | 2.0  | 2.4  |
|--------------|------|------|------|------|------|------|------|------|
| <b>65</b>    | 1440 | 1680 | 1890 | 2100 | 2310 | 2490 | 2760 | 3000 |
| <b>50</b>    | 1515 | 1765 | 1985 | 2205 | 2430 | 2615 | 2900 | 3150 |
| <b>40</b>    | 1560 | 1820 | 2050 | 2275 | 2505 | 2700 | 2990 | 3250 |
| <b>30</b>    | 1660 | 1935 | 2175 | 2415 | 2660 | 2865 | 3175 | 3450 |
| <b>10 LT</b> | 1930 | 2255 | 2535 | 2815 | 3100 | 3340 | 3700 | 4020 |
| <b>10 HT</b> | 1660 | 1935 | 2175 | 2415 | 2660 | 2865 | 3175 | 3450 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.