


FL 639

| | |
|---------------------|--|
| TIRE SIZE | 850/40 R 26.5 |
| UM | US STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | MAȘINĂ DE ÎMPRĂȘTIAT / MAȘINI DE IMPLEMENTARE |
| VERSION | STANDARD |
| TIRE TYPE | TL |
| LI/SS | 173 D ; 184 A8 |



DIMENSIUNI US STANDARD

| | | | |
|-----------------|----------|----------------|-----------------|
| USA CODE | 94064779 | RC (IN) | 162.3 |
| SW (IN) | 33.9 | RIM REC | AG 28.00 |
| OD (IN) | 53.3 | ECE | E11-106R-006228 |
| SLR (IN) | 23.6 | | |

LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 12 | 17 | 23 | 29 | 35 | 41 | 46 | 52 | 58 |
|-----------|------|-------|-------|-------|-------|-------|-------|-------|-------|
| 45 | 4180 | 5360 | 6660 | 7570 | 8740 | 9920 | 10820 | 11870 | 13040 |
| 40 | 4590 | 5870 | 7310 | 8310 | 9600 | 10890 | 11890 | 13040 | 14330 |
| 30 | 5560 | 7110 | 8850 | 10060 | 11620 | 13180 | 14400 | 15780 | 17340 |
| 25 | 6350 | 8130 | 10120 | 11510 | 13290 | 15080 | 16470 | 18050 | 19840 |
| 20 | 6930 | 8870 | 11040 | 12550 | 14510 | 16450 | 17970 | 19700 | 21640 |
| 15 | 7250 | 9290 | 11550 | 13140 | 15180 | 17220 | 18790 | 20610 | 22640 |
| 5 | 8260 | 10580 | 13160 | 14970 | 17280 | 19610 | 21420 | 23480 | 25790 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.