

# AS 504

|                           |   |
|---------------------------|---|
| <b>TIRE SIZE</b>          | <b>5.00 - 15</b>  |
| <b>UM</b>                 | US STANDARD   |
| <b>CONSTRUCTION</b>       |   |
| <b>MACHINERY</b>          | TELEHANDLER / FIELD TRAILER /<br>IMPLEMENTS / TELEHANDLER |
| <b>VERSION</b>            | STANDARD  |
| <b>TIRE TYPE</b>          | TT  |
| <b>LI/SS DRIVE WHEEL</b>  | 75 A8   |
| <b>LI/SS FREE ROLLING</b> | 88 A8   |



## DIMENSIONS US STANDARD

|                 |          |                |                     |
|-----------------|----------|----------------|---------------------|
| <b>USA CODE</b> | 94019151 | <b>RC (IN)</b> | 77.0                |
| <b>SW (IN)</b>  | 5.5      | <b>RIM REC</b> | 3.50 D              |
| <b>OD (IN)</b>  | 25.9     | <b>RIM ALT</b> | 3.00 D; 4.00 E; 4 J |
| <b>SLR (IN)</b> | 12.1     | <b>ECE</b>     | E4-106R-001950      |

## LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 51   |
|-----------|------|
| 5 FR      | 1730 |
| 15 FR     | 1470 |
| 20 FR     | 1380 |
| 25 FR     | 1230 |
| 5 DW      | 1190 |
| 15 DW     | 1010 |
| 20 DW     | 950  |
| 25 DW     | 850  |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.