

# EARTHMAX SR 46

|                  |                         |
|------------------|-------------------------|
| <b>TYRE SIZE</b> | <b>33.00 R 51</b>       |
| <b>UM</b>        | US STANDARD             |
| <b>MACHINERY</b> | RIGID DUMP TRUCK        |
| <b>VERSION</b>   | HEAT RESISTANT COMPOUND |
| <b>TL/TT</b>     | TL                      |
| <b>LI/SS</b>     | 235 B                   |



## DIMENSIONS US STANDARD

|                 |          |                    |           |
|-----------------|----------|--------------------|-----------|
| <b>USA CODE</b> | 94067350 | <b>RIM REC</b>     | 24.00/5.0 |
| <b>OD (IN)</b>  | 120.1    | <b>TRA CODE</b>    | E4        |
| <b>SLR (IN)</b> | 55.2     | <b>STAR RATING</b> | ★★        |
| <b>RC (IN)</b>  | 369.2    |                    |           |

## LOAD CAPACITY (LBS/TYRE)

| MPH / PSI | 73    | 76    | 80    | 83    | 87    | 91    | 94    | 98    | 102   |
|-----------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
| 30        | 66000 | 68000 | 71500 | 74000 | 76000 | 78500 | 80500 | 82500 | 85500 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.