


AW 711

TYRE SIZE	265/70 R 16.5
UM	IS STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	HAY HARVESTER / IMPLEMENT MACHINERY / HARVESTER / IMPLEMENTS
VERSION	STUBBLE RESISTANT
TL/TT	TL
LI/SS	134 A8/B



DIMENSIONS IS STANDARD

SW (MM)	264	RIM REC	8.25
OD (MM)	773	ECE	E11-106R-002978
SLR (MM)	343	SRI	370
RC (MM)	2286		

LOAD CAPACITY (KG/TYRE)

KM/H / BAR	0.8	1.2	1.6	2.0	2.4	2.8	3.2	3.6	4.0
50	680	895	1085	1255	1445	1635	1760	1930	2120
40	680	895	1085	1255	1445	1635	1760	1930	2120
30	760	1000	1215	1405	1615	1830	1975	2165	2375
25	810	1065	1290	1490	1720	1945	2100	2300	2525
20	860	1125	1365	1580	1820	2060	2225	2435	2675
10	955	1250	1515	1755	2020	2290	2470	2705	2970

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.